


(54) Title: DISPLAY DEVICE COMPRISING A LIGHT GUIDE



A display device is provided with a source for UV radiation. The UV radiation is led into a light guide, and at addressed position(s) where a movable element makes contact with the light guide, the UV light exits the light guide and enters the movable element. The movable element is provided with scattering particles which scatter more efficiently in the light than in visible light. Scattered UV light impinges on UV-sensitive phosphor elements. In alternative embodiments, the movable element is provided with phosphor particles embedded in the

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Display device comprising a light guide.

The invention relates to a display device with a light source and a display part comprising a light guide, a movable element and selection means to locally and selectively bring said movable element into contact with the light guide to couple light out of the light guide.

5

A display device of the type mentioned in the opening paragraph is known from United States patent US 4,113,360.

In said patent, a description is given of a display device comprising a first plate of a fluorescent material, in which, in operation, light is generated and trapped (so that this plate forms a light guide), a second plate which is situated at some distance from the first plate and, between said two plates, a movable element in the form of a membrane. By applying voltages to addressable electrodes on the first and second plates and to electrodes on the movable element, the movable element can be locally brought into contact with the first plate, or the contact can be interrupted. A transparent contact liquid is present on the contact surfaces. At locations where the movable element is in contact with the first plate, light is decoupled from said first plate. This enables an image to be represented. If the movable element is not in contact with the light guide, it is in contact with the second plate.

Contrast is a very important parameter by which the quality of a display can be judged. Light which is incident on the display screen of the display is reflected and reduces the visibility of, or blurs the image displayed on the display screen. Simplicity of design is also an important parameter.

It is an object of the invention to increase the contrast of the image displayed by the display part and yet to provide a relatively simple design.

To this end, the display device in accordance with a first aspect of the invention comprises a source for UV radiation, the movable element comprises means for scattering UV light, the display device comprises phosphor elements for emitting visible light at different

colors when excited by UV radiation, and the phosphor elements comprise phosphor particles in an embedding material. Preferably, the phosphor particles have an average size a smaller than λ/π , most preferably between $\lambda/6\pi$ and $\lambda/2\pi$.

By using UV excitable phosphor elements for generating different colors, it is possible to generate a color image. When the movable element is in contact with the light guide, the scattering centers in the movable element scatter the UV light out of the light guide, which UV light excites a phosphor element. The use of phosphors emitting different colors provides a color display device which uses a single type of light source. It is not necessary to use three different types of light sources (one for each color) or to use color filters for extracting colored light from white light, which inevitably results in appreciable losses of intensity.

By placing the phosphor particles in an embedding material (also called matrix), the scattering of all light including visible light by the phosphor element is reduced when using phosphor particles in the usual powder form. The difference in index of refraction between the phosphor particles and its surrounding medium is decreased, which reduces the scattering. In the preferred embodiment, the average size is small (smaller than λ/π , most preferably between $\lambda/6\pi$ and $\lambda/2\pi$) which reduces the scattering. The UV absorption is roughly proportional to a/λ , whereas the scattering is much more strongly reduced as the size of the particles decreases. In the indicated range for the size of the phosphor particles, an efficient UV absorption is combined with a strongly reduced visible light scattering efficiency.

In a second aspect of the invention, the display device comprises a source for UV radiation, the movable element comprises particles for scattering light in an embedding material, and the display device comprises phosphor elements for emitting visible light at different colors when excited by UV radiation, the particles for scattering UV light in the embedding material having a scattering efficiency for the UV radiation emitted by the source, which is larger than the scattering efficiency for light in the visible range, preferably at least twice larger.

Within the framework of the invention the scattering efficiency of light in the visible range is considered to be the scattering efficiency for green light to which the human eye is most sensitive.

The inventors have realized that the nature of the particles for scattering may pose a problem in relation to contrast. Light incident on the scattering particles is in part scattered back to the viewer, which reduces the contrast. Scattering particles in a powder form or when placed on a surface scatter light in a wide range of frequencies. A second aspect of the

invention provides scattering particles which have an appreciably larger scattering efficiency in the UV region than for visible light. Thus, the UV light is coupled out of the light guide by scattering in an efficient manner, and yet incident light is much less efficiently scattered.

In preferred embodiments, the average size a of the scattering particles in the movable element is smaller than λ/π , where λ is the wavelength of the UV radiation emitted by the source. For UV sources emitting UV light in lines, 'the wavelength' is the most prominent component of the spectrum emitted by the source. For UV sources emitting a continuous spectrum, 'the wavelength' is the peak of the continuous spectrum. For particles, the scattering efficiency (when in a matrix) is reduced sharply (roughly by a factor of $(a/\lambda)^k$ (k between 2 and 4)) for wavelengths larger than a . If e.g. $\lambda=380$ nm and $a/\lambda \ll 1$, then $k=4$ and the scattering efficiency for green light ($\lambda=550$ nm) is a factor of 4.4 less than that for UV. Preferably, at least 90 % of the particles is smaller than λ/π . The most preferred range for the average particle size a lies between $\lambda/6\pi$ and $\lambda/2\pi$. If the particles become smaller than $\lambda/6\pi$, the scattering efficiency for UV light decreases strongly. The reduced scattering can be overcome by increasing the number of particles (the density of the particles). This may lead, however, to agglomeration of the particles, the agglomerates forming, in effect, particles of a much larger size, for which the visible light scattering efficiency may be high.

In embodiments of the invention as regards its second aspect, the difference in index of refraction of the scattering particles and the embedding material is larger in UV than in visible light, preferably at least $\sqrt{2}$ larger. The larger the difference in index of refraction, the greater the scattering. By choosing scattering particles and embedding materials for which the difference in index of refraction is larger in UV than in visible light, the ratio of the scattering efficiencies in UV and in visible light is larger than one, thus increasing contrast.

To increase contrast and yet provide an even simpler design, the display device in accordance with a third aspect of the invention comprises a source for UV radiation, and the movable element comprises phosphor particles for emitting visible light at different colors when excited by UV radiation. Preferably, the phosphor particles are embedded in the material of the movable element. In preferred embodiments, the phosphor particles have an average size which is smaller than λ/π , where λ is the wavelength of the UV radiation emitted by the source. Preferably, the phosphor particles have an average size between $\lambda/6\pi$ and $\lambda/2\pi$.

By providing the phosphor particles directly in or on the movable element, the design is simplified, because separate phosphor-comprising elements need no longer be used. Compared to embodiments in which the UV light is scattered in the movable element, exits

this element and thereafter impinges on phosphor elements, no scattering particles are needed, which reduces the scattering of visible light, and more of the UV light can be used for exciting the phosphors, thus reducing the amount of phosphor material needed and thus further reducing scattered light by reducing the light scattered by the phosphor particles. By
5 embedding the phosphor particles in the material of the movable element, scattering of visible light is further reduced. The indicated size ranges provide an even further reduced scattering of visible light.

10 These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter. In the drawings:

 Fig. 1 is a cross-sectional view of a display device in accordance with the invention;

 Fig. 2 shows a detail of the display device shown in Fig. 1;

15 Fig. 3 illustrates scattering of UV light in the movable element, which impinges on a separate phosphor element;

 Fig. 4 illustrates an embodiment of the second aspect of the invention, i.e. a display device having phosphor particles in the movable element;

20 Fig 5 is a plan view of the display device shown in Fig. 1, showing how the display device is driven.

 The Figures are schematic and not drawn to scale, and, in general, like reference numerals refer to like parts.

25 Fig. 1 schematically shows a display device 1 in accordance with the invention. Said display device comprises a light guide 2, a movable element 3 and a second plate 4. Electrode systems 5 and 6 are arranged, respectively, on the sides of the light guide 2 and the second plate 4 facing the movable element 3. By locally generating a potential difference between the electrodes 5, 6 and the movable element 3, by applying, in operation, electric
30 voltages to the electrodes and the movable element forces are locally exerted on the movable element, which pull the movable element against the light guide or keep it at a distance from the light guide, preferably against the second plate 4. The display device further comprises a light source 9 which in operation emits UV light. Reflectors 10 are provided. Fig. 2 shows how the movable element 3 lies against the light guide 2. In this state, a portion of the UV

light enters the movable element. In this movable element, the UV light is scattered, so that part of the UV light leaves the display device. The light may exit at both sides or at one side. In Fig. 2, this is indicated by means of arrows. The display device comprises color-determining phosphor elements 20. UV light leaves the light guide at the addressed position, enters movable element 3, is scattered, and at least part of the UV light leaves the movable element and is incident on phosphor elements. The phosphor elements, excited by the UV light, emit colored light. The use of UV light and phosphor elements increases the efficiency of the display device.

Using a UV light source and phosphor elements which, when excited by UV light, emit light of different colors has the advantage that only a single type of light source needs to be used, and it is not necessary to use absorbing color filters for converting white light into colored light of a particular color by absorbing other colors. Such color filters result in an appreciable loss of efficiency.

Within the concept of the invention it is possible and even preferred to use light filters or light-filtering elements. However, such preferred light filters would mainly absorb light outside the relevant color range for phosphor elements, so that the contrast and/or the color point of the emitted light can be improved. For example, a red light-emitting phosphor element may be provided with a color filter for absorbing green and/or blue light. This has the advantage that the contrast is improved because most of the incident light is absorbed while the emitted light intensity is hardly reduced. Likewise, a blue light-emitting phosphor element may be provided with green and/or red light-absorbing material. Such color filters may comprise added absorbing layers or absorbing materials (such as pigments) added to the phosphor elements. If absorbing layers are used, the phosphor elements are positioned between the absorbing layer and the movable element. The UV light does not pass the absorbing layer. Absorption of UV light (with resulting loss of efficiency) does not occur. In contrast, absorbing materials in the phosphor elements (especially blue light-absorbing materials) may cause appreciable absorption of UV light.

Figure 3 shows in more detail a movable element 3 and a light guide 2. When the movable element makes contact with an insulating layer 11 on electrode 5, UV light is capable of entering the movable element 3. The UV light is scattered by scattering particles 21 in the matrix (for instance a polymer matrix) of the movable element 3. The scattered UV light exits the movable element 3 and a portion of it impinges on phosphor element 20 which comprises a UV excitable phosphor, which emits visible light upon excitation, in this example blue light B seen by viewer V. The intensity of the light emitted by the phosphor element is

dependent on the efficiency with which the UV light is scattered by the particles 21. Apart from scattering the UV light, the phosphor elements as well as the UV scattering particles may, however, also scatter incident light I_{in} , resulting in a scattered light intensity I_{out} . This scattered light reduces the contrast of the displayed image. Scattering particles in the form of a powder (for instance, a powder layer) on movable element 3 have a high visible light scattering efficiency. Such layers are in effect approximately white scattering layers, i.e. scattering equally well at all wavelengths. By having scattering particles in an embedding material, such as - but not restricted to - a polymer layer, the ratio of the scattering efficiency for UV light and for visible light can be appreciably higher than one, preferably above two.

In a first aspect of the invention, the phosphor elements 20 comprise phosphor particles 22 in an embedding material, the phosphor particles preferably having an average size smaller than λ/π , most preferably between $\lambda/6\pi$ and $\lambda/2\pi$. By placing the phosphor particles in an embedding material, for instance a polymer matrix, the scattering of all light including visible light is reduced when using phosphor particles in a powder form. The difference in index of refraction between the phosphor particles and its surroundings is decreased, which reduces the scattering. Preferably, the matrix in which the phosphor particles are embedded has a high index of refraction in visible light (higher than 1.5, preferably higher than 1.8, more preferably substantially equal to the index of refraction of the phosphor particles). Furthermore, because they are in a matrix, agglomeration of particles is reduced and thus decreases the effective size distribution which positively influences the scattering. The UV absorption is roughly dependent on a/λ . In the indicated range for the size of the phosphor particles, an efficient UV absorption is combined with a strongly reduced visible light-scattering efficiency.

The contrast can also be improved additionally or separately if in particular the average size a of the scattering particles is smaller than λ/π , where λ is the wavelength of the UV radiation emitted by the source. For UV sources emitting UV light in lines, 'the wavelength' is the most prominent component of the spectrum emitted by the source. For UV sources emitting a continuous spectrum, 'the wavelength' is the peak of the continuous spectrum. For particles, the scattering efficiency (when in a matrix) is reduced sharply (roughly by a factor of $(a/\lambda)^k$ (k between 2 and 4)) for wavelengths larger than a . For $a \ll \lambda/2\pi$, the scattering efficiency is proportional to $(a/\lambda)^4$. Preferably, at least 90 % of the particles is smaller than λ/π . The most preferred range for the average particle size a lies between $\lambda/6\pi$ and $\lambda/2\pi$. If the particles become smaller than $\lambda/6\pi$, the scattering efficiency for UV light

becomes small. The reduced scattering can be overcome by increasing the number of particles (the density of the particles). This may lead, however, to agglomeration of the particles, the agglomerates forming, in effect, particles of a much larger size, for which the visible light-scattering efficiency may be high.

5 In embodiments of the invention, the difference in index of refraction between the material from which the scattering particles are made and the embedding material is larger for UV radiation than for visible light. The scattering efficiency (i.e. the amount of light scattered by the particles) is then larger for UV light than for visible light. Such a situation can be achieved by choosing a material for either the scattering particles or the embedding
10 material, preferably for the scattering particles for which the optical band gap has smaller wavelengths but is close to the wavelength of UV light emitted by the UV source. The index of refraction close to an optical band gap is large and strongly dependent on the wavelength, leading to a much larger difference in index of refraction near the optical band gap than far remote from the optical band gap

15 Figure 4 shows an embodiment of another aspect of the invention. In this embodiment, the movable element 3 comprises UV-sensitive phosphor particles 22. When the movable element is in contact with the light guide 2, UV light enters the movable element 3 and is converted into visible light B seen by viewer V. This embodiment has a number of advantages:

- 20 • It is simpler, because there is no need for color-determining elements 20.
- In Figure 3, at least some of the UV light exiting the movable element does not enter an element with phosphor particles. In Figure 4, all (or at least a greater part) of the UV light entering movable element 4 enters an element having phosphor particles. Thus the portion of UV light converted is generally larger, so that fewer phosphor particles are needed,
25 reducing unwanted scattering of visible light by the phosphor particles.
- Many materials absorb at least some UV light. On average, compared to the embodiment of Figure 3, the UV light has to traverse less of movable element 3 and or/of color determining element 20. Thus, a wider range of materials is suitable for movable element 3.
- 30 • The reflection of light on the outer surface of movable element 3 (the surface facing electrode 6) is generally larger for UV light than for visible light.

In preferred embodiments, the movable element is also provided with absorbing materials to absorb light of colors different from those emitted by the phosphor particles. The parts of the movable element having red light-emitting phosphor particles are therefore preferably

provided with materials such as pigments to absorb green and/or blue light. This increases the contrast.

Fig. 5 is a plan view of an embodiment of the display device shown in Fig. 11. The electrodes 5 and 6 form a matrix structure. From a control unit 17, which comprises selection means, selection signals (electric voltages) are supplied to the electrodes 5 and 6 via connections 15 and 16. This set of selection signals determines the potentials V_5 and V_6 on the electrodes 5 and 6, which are preferably covered by an insulation layer. Furthermore, a voltage V_3 can be applied to the element 3. By applying suitable potential differences to the electrodes 5 and 6 and element 3, the movable element 3 can be actuated, in operation, from and to the electrodes 5 and 6 at the location of selected crossings of the electrodes 5 and 6. In this example, electrodes 5 form column electrodes, i.e. electrodes extending in the 'short' direction of the rectangular display, while electrodes 6 form the row or line electrodes, i.e. electrodes extending in the 'long' direction of the rectangular display.

In summary, the invention can be described as follows. A display device is provided with a source for UV radiation wherein the UV radiation is led into a light guide, and at addressed position(s) where a movable element makes contact with the light guide, the UV light exits the light guide and enters the movable element. In a first aspect of the invention, the phosphor elements comprise phosphor particles which are embedded in a matrix material and preferably have a small size. In a second aspect of the invention, the movable element is provided with scattering particles which scatter more efficiently in UV light than the visible light. Scattered UV light impinges on UV-sensitive phosphor elements. In alternative embodiments, the movable element is provided with phosphor particles embedded in the material of the movable element. In all aspects, pigment particles (preferably with an average particle size $< \lambda/\pi$) are provided.

CLAIMS:

1. A display device with a light source and a display part comprising a light guide, a movable element and selection means to locally and selectively bring said movable element into contact with the light guide to couple light out of the light guide, characterized in that the light source is a source for UV radiation, the movable element comprises means for scattering
5 UV light, the display device comprises phosphor elements for emitting visible light at different colors when excited by UV radiation, and the phosphor elements comprise phosphor particles in an embedding material.

2. A display device with a light source and a display part comprising a light guide, a movable element and selection means to locally and selectively bring said movable element into contact with the light guide to couple light out of the light guide, characterized in that the light source is a source for UV radiation, the movable element comprises scattering particles for scattering light in an embedding material, and the display device comprises phosphor
10 elements for emitting visible light at different colors when excited by UV radiation, the particles for scattering UV light in the embedding material having a scattering efficiency for the UV radiation emitted by the source, which is larger than the scattering efficiency for light in the visible range.

3. A display device as claimed in claim 2, characterized in that the scattering
20 efficiency of the particles is at least twice that for visible light.

4. A display device as claimed in claim 1 or 2, characterized in that the average size a of the phosphor particles and/or scattering particles is smaller than λ/π , where λ is the wavelength of the UV radiation emitted by the source.

5. A display device as claimed in claim 4, characterized in that at least 90 % of the particles is smaller than λ/π .

6. A display device as claimed in claim 4, characterized in that the average particle size a lies between $\lambda/6\pi$ and $\lambda/2\pi$.


7. A display device as claimed in claim 2, characterized in that the difference in index of refraction between the embedding material and the material of the scattering particles is larger for UV radiation than for visible light.

8. A display device as claimed in claim 1, characterized in that the device comprises color filter elements.

9. A display device with a light source and a display part comprising a light guide, a movable element and selection means to locally and selectively bring said movable element into contact with the light guide to couple light out of the light guide, characterized in that the light source is a source for UV radiation, and the movable element comprises particles in an embedding material for converting UV light into visible light.

10. A display device as claimed in claim 11, characterized in that the phosphor particles have an average size which is smaller than λ/π , where λ is the wavelength of the UV radiation emitted by the source.

11. A display device as claimed in claim 10, characterized in that the phosphor particles have an average size between $\lambda/6\pi$ and $\lambda/2\pi$.






FIG. 2




FIG. 4

3/4




FIG. 3

4/4




FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/00336

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G02B26/02 G09F9/37

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G02B G09F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	WO 98 19201 A (XEOTRON CORP ;ZHOU XIAOCHUAN (US)) 7 May 1998 (1998-05-07) page 16, line 8 - line 25 page 31, line 14 - line 17 figures 6C,20	1,9 2,8
A	US 5 771 321 A (STERN ERNEST) 23 June 1998 (1998-06-23) column 14, line 58 - line 67 column 15, line 1 - line 27 figures	1,2,9
A	US 4 113 360 A (BAUR GUENTER ET AL) 12 September 1978 (1978-09-12) cited in the application abstract; figures	1,2,9

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

25 April 2000

Date of mailing of the international search report

03/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.

Authorized officer

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/00336

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9819201 A	07-05-1998	AU 5156198 A US 5953469 A	22-05-1998 14-09-1999
US 5771321 A	23-06-1998	CA 2241823 A EP 0888573 A WO 9731288 A	28-08-1997 07-01-1999 28-08-1997
US 4113360 A	12-09-1978	NONE	